



NOTES:

1. REFER TO THIS DETAIL WHEN INSTALLING NEW SERVICE LATERALS TO NEW MANHOLES.
2. ROUTE ALL NEW SERVICE LATERALS BEING INSTALLED TO NEW MANHOLES SUCH THAT THE SERVICE LATERAL CROWN ELEVATION MATCHES THE HIGHEST CROWN ELEVATION OF THE CONNECTING SEWER(S). CONTRACTOR SHALL USE BENDS AS NECESSARY. DROP PIPES INSIDE MANHOLES SHALL NOT BE ALLOWED.

THE INVERT CHANNEL FOR THE NEW LATERAL SHALL BE FORMED AND POURED AS PART OF THE MAIN PRECAST INVERT CHANNEL AND SHALL MEET ALL REQUIREMENTS SHOWN IN DETAIL WW-1.

3. IF THE HOLE FOR THE SERVICE LATERAL MUST BE CORE-DRILLED IN THE FIELD AND A FLEXIBLE RUBBER BOOT CONNECTOR CANNOT BE USED, REFER TO DETAIL WW-17 FOR REQUIREMENTS.

**GREER COMMISSION OF PUBLIC WORKS
NEW SERVICE LATERAL TO NEW MANHOLE**

APPROVED BY: --		DATE: FEBRUARY 2021	DRAWING NO. WW-16
SCALE: NTS		REVISED: --	